

TECHNICAL DATA

RTD Chlorine Free Spray Metal Cutting Lubricant Spray

Description

ROCOL RTD Chlorine Free Spray is an aerosol applied metal cutting lubricant consisting of a concentrate of extreme pressure additives. Rocol RTD Chlorine Free Spray applies an economical film of metal cutting fluid directly to the cutting zone and is particularly suitable for use during machining operations and in areas where access is difficult.

Outstanding Features

- ? **Superb cutting performance**
- ? **Suitable for all ferrous metals**
- ? **Ideal for reaming, tapping, drilling and general workshop operations**
- ? **Fast and convenient application**

Directions for use

Shake well before use and spray directly onto workpiece or tool from a distance of 15 - 30 cm. Test compatibility with painted or coated surfaces, plastics and rubbers prior to application. Ensure adequate ventilation.

Technical Data

<i>Appearance</i>	: <i>Red</i>
<i>Propellant</i>	: <i>Hydrocarbon blend</i>
<i>Solvents</i>	: <i>Solvent free</i>
<i>Shell 4 Ball - Weld Load</i>	: <i>>800kg</i>
<i>Silicones</i>	: <i>None</i>
<i>Storage</i>	: <i>Storage temperature should be kept below 50°C. Storage area should be out of direct sunlight.</i>
<i>Pack Sizes</i>	: <i>400ml</i>

Further Technical Data and Health and Safety information (MSDS) is available from:

