

TEROSON WX 210

Known as Multi Wax Spray April 2014

PRODUCT DESCRIPTION

TEROSON WX 210 provides the following product characteristics:

Application	Anticorrosive Agent
Technology	High Quality Anti-Corrosion Agent in a Spray Can for Area Coating and Cavity Protection
Basis	Waxes, Polymers and Anti-Rust additives

TEROSON WX 210 is an anti-corrosion agent for area coating and for the protection of cavities, containing mild smelling solvents. It is a thin, slightly thixotropic spray which atomizes easily. The anticorrosion agent is bitumen free and has a strong neutralisation power and thus good acid binding capacity. The product contains a high proportion of rust inhibitors. The polymer portion leads to high toughness and relative high abrasion resistance compared to other wax products.

TEROSON WX 210 is very finely atomized on spraying, has outstanding creep qualities, penetrates well into the spaces to be protected (e.g. welds) and yet does not run excessively from the bottom of such joints. Creep qualities are optimal if the product and the bodywork are at room temperature.

When fully dry, the anti-corrosion agent forms a tough, plastic, water-repellent film of translucent thin layers.

The aerosol can is equipped with two spray heads: one spray head with a tube, one spray head with a slit nozzle for area coating.

APPLICATION AREAS

TEROSON WX 210 is used in workshops primarily as conservation wax for preventive protection and for care and repair.

With the new type of fan jet spraying head underbodies of cars can be evenly coated with a widespread jet.

The attached round jet spraying head with tube allows spraying in cavities on cars, e.g. doors, motor hoods, trunk lids and areas difficult to reach. TEROSON WX 210 is suitable for spraying the interior of open cavities, in addition to existing cavity conservation of new vehicles and follow-up treatment after accident repairs. The product is ideal for corrosion protection on sheet metal and steel parts, e.g. fuel tanks, brake tubes or tubes of the power assisted steering. Screw connections at gearbox crossrails and engine suspensions can also be coated with this translucent protection film. The thread is thus protected and will enable

secure screwing.

On modern cars TEROSON WX 210 completes the factory coating on transitions, under plastic hoods, in the wheel houses and under the fenders. The splash water resistant film permanently protects concealed body areas. Body seams under bumpers which are no longer caulked in the factory can be securely sealed.

TEROSON WX 210 is particularly suitable for long term protection of immobilized vehicles. The product is also used for the conservation of seams, areas and cavities on vehicles and rust endangered spots in the engine compartment. Slightly sprayed rubber parts will show a dull gloss and a fresh appearance.

Building machinery, agricultural equipment and gardening implements, e.g. the underbody of lawn mowers, hoes and spades can also be excellently maintained and protected.

TECHNICAL DATA

(Typical Test Results)

Colour	beige-translucent
Odour	mild odour
Density	approx. 0.85 g/cm ³
Solid	approx. 40 %
Consistency	thin liquid, slightly thixotropic
Drop point of solid (DIN 51801)	>100 °C
Sag resistance	min. 100 µm
Penetration	>13 mm
Behaviour in the repair paint oven (1.5 hrs at 90°C)	no running off
Corrosion resistance	no corrosion
salt spray test to DIN 50021 (35°C, salt solution 5%, 240 hrs)	
Dry film thickness	50 µm
Application temperature	15 to 25 °C
In service temperature	-40 to 100 °C
Short exposure (up to 1 h)	130 °C

TEROSON WX 210

Known as Multi Wax Spray April 2014

PRELIMINARY STATEMENT

Prior to application it is necessary to read the **Material Safety Data Sheet** for information about precautionary measures and safety recommendations. Also, for chemical products exempt from compulsory labeling, the relevant precautions should always be observed.

Preparation

Any items of trim and covers should be removed. Any rust should be removed as far as possible. To spray awkward areas (e.g. semi-hollow zones such as doors etc.), the special spray head with the tube is used. The material should be at room temperature when used. If stored for long periods and if the material is at a temperature below 15°C, the material becomes more thixotropic. Therefore the can should be shaken vigorously before use until the ball-bearing becomes audible.

Spraying

The body parts (which should be free from dust and grease) should be sprayed evenly, with the can held upright during spraying. When using the spray tube, this can be moved slowly in circles whilst spraying so that all directions are covered.

After use the can should be held with the valve down and the spray should be activated until the jet is cleared and only propellant is emitted.

Cleaning

Any escaping TEROSON WX 210 can be wiped off easily. Engine Wash is suitable for cleaning partially dried material. Any splashes onto painted surfaces should be removed immediately.

Note

As TEROSON WX 210 contains a combustible propellant gas, care should be taken to allow good air access before closing the cavity off (e.g. door trim) and assure good aeration during drying phase (depending on the cavity the drying period can last up to several days). Power-window switch may only be manipulated after completion of aeration.

STORAGE

Frost sensitive	no
Recommended storage temperature	15 to 25 °C; (never heat above 50 °C!)
Shelf life	18 months

Disclaimer**Note:**

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. The product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

In case products are delivered by Henkel Belgium NV, Henkel Electronic Materials NV, Henkel Nederland BV, Henkel Technologies France SAS and Henkel France SA please additionally note the following:

In case Henkel would be nevertheless held liable, on whatever legal ground, Henkel's liability will in no event exceed the amount of the concerned delivery.

In case products are delivered by Henkel Colombiana, S.A.S. the following disclaimer is applicable:

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

TEROSON**TEROSON WX 210**

Known as Multi Wax Spray April 2014

In case products are delivered by Henkel Corporation, Resin Technology Group, Inc., or Henkel Canada Corporation, the following disclaimer is applicable:

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein and to adopt such precautions as may be advisable for the protection of property and of persons against any hazards that may be involved in the handling and use thereof. In light of the foregoing, **Henkel Corporation specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits.** The discussion herein of various processes or compositions is not to be interpreted as representation that they are free from domination of patents owned by others or as a license under any Henkel Corporation patents that may cover such processes or compositions. We recommend that each prospective user test his proposed application before repetitive use, using this data as a guide. This product may be covered by one or more United States or foreign patents or patent applications.

Trademark usage

Except as otherwise noted, all trademarks in this document are trademarks of Henkel Corporation in the U.S. and elsewhere. ® denotes a trademark registered in the U.S. Patent and Trademark Office.

Henkel AG & Co. KGaA

D-40191 Düsseldorf, Germany
Phone: +49-211-797-0
www.henkel.com

Henkel Central Eastern Europe GmbH

A-1030 Wien, Austria
Phone: +43-1711-040
www.henkel.com

Henkel & Cie AG

CH-4133 Pratteln, Switzerland
Phone: +41-61-825-7000
www.henkel.com

